






Mini-ITX Embedded Motherboard based on Intel Atom D2700 Processor



Specification:

Model No.	EMB-ID2700Y-MI26
Processor	Integrated Intel®Atom D2700 2.13G dual core processor
Chipset	Adopt Intel® NM10 high speed chipset
Memory	1 x DDR3 SODIMM memory slot, supports 800/1066MHz memory, up to 4GB
Graphics	Integrated Intel® GMA3600 graphics
	1 x VGA, 1 x LVDS (supports single channel 24BIT)
	Supports VGA; LVDS synchronous/Asynchronous display
Network	2 x RTL8111F Gigabit Ethernet, supports wake on LAN/PXE function
Storage	1 x SATA2.0 HDD port, the transfer rate up to 3Gbps
	1 x MSATA slot, supports SSD, the transfer rate up to 3Gbps
Audio	Integrated ALC662 6-channel high fidelity audio controller, supports MIC, Line_out
Expansion Slot	1 x PCI slot
	1 x Mini-PCIE slot, supports WIFI, USB WIFI
Rear I/O	1 x 12V DC JACK power input port
	1 x PS/2 KB/MS port
	4 x USB2.0
	2 x RJ-45 gigabit ethernet ports
	1 x double standard audio port (supports MIC, Line out)
	1 x LPT
	1 x VGA
	1 x RS232 serial port (1/9pin supports 5V/12V charged function)
Internal I/O	1 x HDD power supply port
	4 x USB2.0
	5 x RS232 serial ports
	1 x Front panel audio port 2 x 5pin
	1 x single 24Bit LVDS port
	1 x screen power supply port 1 x 6pin
	1 x front panel function buttons and indicator port 2 x 5pin
	1 x JVGA1 2 x 5pin, the same signal with DB15
1 x 4pin ATX 12V power port	
Fan Interface	Supports fanless cooling, reserved 1 x 3pin CPU connector, 1 x 3pin system connector
BIOS	16Mb Flash ROM
Watch Dog	Supports hardware reset function (L256, 0~255 seconds)
OS	Windows 7
Power Input	Adopt DC 12V power supply
Working Temp.	-10°C ~ 60°C
Storage Temp.	-20°C ~ 70°C
Working Humidity	5%-95% relative humidity, non-condensing
Dimension	170mm x 170mm

Order Information:

Processor	Frequency	Memory	VGA	LVDS	LAN	USB	COM	RS485/422	Power
D2700	2.13G	1 x SODDDR3	1	1 x 24Bit	2 x RTL8111f	8	6	X	DC12V

ABOUT POLYHEX

