

Industrial Box PC Based on Intel i7-4500U CPU, supporting Haswell & Broadwell Celeron/Pentium/i3/i5/i7 Low Voltage Processors

Main Features:

- · Industrial grade chassis, stable, dust-proof and vibration-proof
- · Passive cooling, silent and hardware automatic power up
- · Supports Haswell & Broadwell Celeron/Pentium/i3/i5/i7 low voltage processors
- · 2 x Intel LAN, 2 x HDMI, 4 x USB 3.0, 2 x USB 2.0
- · 6 x COM (COM2 has 485 option, COM3 has VGA option)
- · SIM slot (optional)
- · Industrial grade motherboard, GPIO 4 input 4 output (optional)
- · Support VESA monitor mount









Specification:

System	
CPU	Intel i7-4500U, 2C/4T, 1.80GHz up to 3.00GHz, 4MB Smart Cache, 15W TDP
Chipset	Intel
GPU	Intel HD Graphics
Memory	1 x SO-DIMM slot, support DDR3L 1333/1600MHz up to 8GB
Storage	1 x 2.5 inches SATA 3.0 (6Gb/s) SSD/HDD slot
Storage	1 x Full-height Mini PCIe mSATA
Audio	ALC662, 16/20/24-bit PCM format
Network	2 x Intel I211-AT Gigabit network
WLAN/Bluetooth	1 x Half-height Mini PCIe WLAN/Bluetooth/3G SIM
I/O Interfaces	
	2 x USB 2.0 (Front)
USB	2 x USB 3.0 (Front)
	2 x USB 3.0 (Back)
COM	6 x RS232 (4 Back+2 Front) (COM2 has RS485 option, COM3 has VGA option)
Display	2 x HDMI
Network	2 x RJ45 10/100/1000Mbps LAN
WLAN	Optional
Audio	1 x Headphone, 1 x Microphone
Power Supply	DCIN
Power Supply Mechanical	DCIN
	Adapter 12V/5A 60W
Mechanical	
Mechanical Power	Adapter 12V/5A 60W
Mechanical Power Cooling	Adapter 12V/5A 60W Fanless, passive cooling
Mechanical Power Cooling LED Light	Adapter 12V/5A 60W Fanless, passive cooling Power LED, HDD LED
Mechanical Power Cooling LED Light Button	Adapter 12V/5A 60W Fanless, passive cooling Power LED, HDD LED Power button
Mechanical Power Cooling LED Light Button Dimension	Adapter 12V/5A 60W Fanless, passive cooling Power LED, HDD LED Power button 187 x 111 x 50mm (L x W x H)
Mechanical Power Cooling LED Light Button Dimension Mounting	Adapter 12V/5A 60W Fanless, passive cooling Power LED, HDD LED Power button 187 x 111 x 50mm (L x W x H)
Mechanical Power Cooling LED Light Button Dimension Mounting Environmental	Adapter 12V/5A 60W Fanless, passive cooling Power LED, HDD LED Power button 187 x 111 x 50mm (L x W x H) VESA mount (optional)
Mechanical Power Cooling LED Light Button Dimension Mounting Environmental Operating Temp.	Adapter 12V/5A 60W Fanless, passive cooling Power LED, HDD LED Power button 187 x 111 x 50mm (L x W x H) VESA mount (optional) 0°C~50°C (industrial grade components)
Mechanical Power Cooling LED Light Button Dimension Mounting Environmental Operating Temp. Storage Temp.	Adapter 12V/5A 60W Fanless, passive cooling Power LED, HDD LED Power button 187 x 111 x 50mm (L x W x H) VESA mount (optional) 0°C~50°C (industrial grade components) -20°C ~70°C
Mechanical Power Cooling LED Light Button Dimension Mounting Environmental Operating Temp. Storage Temp. Relative Humidity	Adapter 12V/5A 60W Fanless, passive cooling Power LED, HDD LED Power button 187 x 111 x 50mm (L x W x H) VESA mount (optional) 0°C~50°C (industrial grade components) -20°C ~70°C
Mechanical Power Cooling LED Light Button Dimension Mounting Environmental Operating Temp. Storage Temp. Relative Humidity Others	Adapter 12V/5A 60W Fanless, passive cooling Power LED, HDD LED Power button 187 x 111 x 50mm (L x W x H) VESA mount (optional) 0°C~50°C (industrial grade components) -20°C ~70°C 5%~95% (non-condensing)
Mechanical Power Cooling LED Light Button Dimension Mounting Environmental Operating Temp. Storage Temp. Relative Humidity Others BIOS	Adapter 12V/5A 60W Fanless, passive cooling Power LED, HDD LED Power button 187 x 111 x 50mm (L x W x H) VESA mount (optional) 0°C~50°C (industrial grade components) -20°C ~70°C 5%~95% (non-condensing) AMI BIOS Windows 7/8/10
Mechanical Power Cooling LED Light Button Dimension Mounting Environmental Operating Temp. Storage Temp. Relative Humidity Others BIOS Operating System	Adapter 12V/5A 60W Fanless, passive cooling Power LED, HDD LED Power button 187 x 111 x 50mm (L x W x H) VESA mount (optional) 0°C~50°C (industrial grade components) -20°C ~70°C 5%~95% (non-condensing) AMI BIOS Windows 7/8/10
Mechanical Power Cooling LED Light Button Dimension Mounting Environmental Operating Temp. Storage Temp. Relative Humidity Others BIOS Operating System Package & Accessori	Adapter 12V/5A 60W Fanless, passive cooling Power LED, HDD LED Power button 187 x 111 x 50mm (L x W x H) VESA mount (optional) 0°C~50°C (industrial grade components) -20°C ~70°C 5%~95% (non-condensing) AMI BIOS Windows 7/8/10



ABOUT POLYHEX

As a board level and system level designer and manufacturer, Polyhex, with 12-year experience, always delivers best-in-class embedded computing solutions based on both ARM and X86 architecture, including hardware customization and software debugging etc. Partnered with silicon vendors like Intel, NXP, ST, Rockchip, Allwinner and so on, we have earned trust from clients worldwide in over 30 countries. Polyhex is also certified with ISO9001 and ISO13485 for the self-owned manufacture facility.

